

### Key Features

- Chemical System: Alkaline-Manganese Dioxide (Zn/MnO<sub>2</sub>)
- Replaces A11, L1016, 11A, GP11A, LR11A, E11A, 4LR932
- High voltage response, stable during most of the lifetime of the application
- Reliable Performance
- Wide operating temperature range
- Low self-discharge with long operating life (<10% after 1 year of storage at + 20 °C)
- Excellent resistance to corrosion
- Designed to meet all major quality, safety and environment standards:
  - Safety: IEC 60086-5
  - Battery Directive 2006/66/EC
  - RoHS and REACH compliance
  - ISO 9001, Duracell World Class Continuous Program

### Typical applications

- Car burglar alarm remotes
- Photographic equipment
- Electric appliance remote control
- Key Fobs
- GPS trackers

Delivered capacity is dependent on the applied load, operating temperature and cut-off voltage. Please refer to the charts and discharge data shown for examples of the energy/service life that the battery will provide for various load conditions.

### Electrical characteristics


- Nominal capacity (22k Ohm Cont., 3.0 V cut-off) 55 mAh
- Open circuit voltage (at + 20 °C) 6.0 V

### Physical characteristics

- Typical weight 4.3 g (0.15 oz.)
- Typical volume 1.26 cm<sup>3</sup> (.08 in<sup>3</sup>)

### Operating conditions

- Operating temperature range -10°C to 60°C (14°F to 140°F)
- Storage temperatures Recommended 5°C to 30°C (41°F to 86°F)



# DURACELL®

BATTERIES

Berkshire Corporate Park  
Bethel, CT. 06801 U.S.A.  
Telephone: Toll-free 1-800-544-5454  
www.duracell.com